

## **Substrate Data Sheet**

# 2010 White Vinyl

General Discription: This is a 2mil cast white vinyl with clear permanent pressure sensitive modified acrylic adhesive and back with a Transparent Synthetic flat release liner.

**Production Data Value Test Method** 

#### **Physical Properties**

Thickness	Film & Adhesive	2.5 to 3.5 mil (0.063 to 0.09mm)	
Applied Shrinkage		0.008in (0.2mm)	n/a
Tensile Strength (mimimum)		5lbs/in @ 73°F (0.9kg/cm @ 23°C)	

### **Adhesion Properties\*\***

Final adhesion value is 24 hours after application			
ABS	4 pounds/inch (0.7kg/cm)	4 pounds/inch (0.7kg/cm)	
Acrylic	4 pounds/inch (0.7kg/cm)		
Acrylic Enamel	4 pounds/inch (0.7kg/cm)	2	2/2
Aluminum, alodine	8 pounds/inch (1.4kg/cm)	TI/	n/a
Chrome	5 pounds/inch (0.9kg/cm)		
Polycarbonate	4 pounds/inch (0.7kg/cm)		
Urethane Paints	4 pounds/inch (0.7kg/cm)		

<b>Chemical Resistance Char-</b>	Resists mild acids, alkalis, and salts
acteritics	Excellent water resistance

Expected Exterior Life			
United States	5 to 8 years		Vertical Exposure: face of graphic is +/- 10 ° from vertical
U.S. Desert Soutwest*	3 to 5 years		Voltion

<sup>\*</sup>The U.S. Desert Southwest includes Arizona, New Mexico, and the desert areas of California, Nevada, Utah, and Texas. The exterior life of the products is reduced due to the high solar energy exposure in these areas.

Service Temperature Range	-40°F to225°F (-40°C to 107°C)		
Minimum Application Temperature	50°F (10°C)		
Storage Stability	Two years when stored at 70°F (21°C) and 50% relative humidity		

#### **Product Performance and Suitability**

All of the descriptive information, the typical performance data, and recommendations for the use of LY.com products shall be used as a guide and do not reflect the specification or specification range for all particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no even constitute a warranty of any kind by LY.com All purchasers of LY.com products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of LY.com is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.